

TITLE: **METHOD FOR PREVENTING ENDLESS TRANSFER OF**
PACKET IN WIRELESS LAN SYSTEM

APPLICANT: **Kiyohito KANEKO**

22511

PATENT TRADEMARK OFFICE

METHOD FOR PREVENTING ENDLESS TRANSFER OF PACKET IN WIRELESS LAN SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

5 **[0001]** The present invention relates to a wireless interconnecting device
which is used in a so-called wireless LAN (Local Area Network) system and a
program which is used therein, in particular, to a method for preventing
endless transfer of a packet in a wireless LAN system, a processing program
10 for preventing endless transfer of a packet, a recording medium on which a
processing program for preventing endless transfer of a packet is recorded, a
wireless interconnecting device, and a wireless LAN system, which can
improve efficiency and so on of packet transfer.

Description of the Related Art

15 **[0002]** As networking of computers is becoming easier than before
according to improvement in performance and price reduction of personal
computers, and so forth, so-called LANs (Local Area Networks) on various
scales are becoming popular.

20 As a form of the LAN, a wireless LAN conforming to IEEE802.11b
which enables connection between terminals and a network via a radio
channel has drawn more attention recently because it has such advantages that
the terminals can be connected with the network regardless of their locations
and that jobs for wiring and the like are very much reduced compared with a
25 so-called wired LAN, and, therefore, various arts related to the wireless LAN
have been proposed (refer to, for example, Japanese Patent Laid-open No. Hei
8-139723, and so forth).

30 In the wireless LAN, a wireless interconnecting device, generally
called an access point, having a function of mediating exchange of packets
between the network and the terminals by communicating with the terminals
via the radio channel is used.

[0003] However, in the wireless LAN, when a plurality of wireless
interconnecting devices are in a state where their communication ranges with
wireless terminals are set to partly overlap each other, a phenomenon unique

to the radio channel sometimes occurs that a wireless interconnecting device receiving a packet transfers the packet to a different interconnecting device based on the judgment that a wireless terminal to which the packet is to be sent does not exist under its control, and thereafter, the transferred packet which is processed in the same way in the different wireless interconnecting device is returned to it again so that packet transfer continues endlessly. This causes a disadvantage that unnecessary traffic occurs.

SUMMARY OF THE INVENTION

[0004] It is an object of the present invention to provide a method for preventing endless transfer of a packet in a wireless LAN system, a processing program for preventing endless transfer of a packet, a recording medium on which a processing program for preventing endless transfer of a packet is recorded, a wireless interconnecting device, and a wireless LAN system which are capable of surely preventing endless packet transfer in the wireless LAN system and realizing efficient traffic.

It is another object of the present invention to provide a method for preventing endless transfer of a packet in a wireless LAN system, a processing program for preventing endless transfer of a packet, a recording medium on which a processing program for preventing endless transfer of a packet is recorded, a wireless interconnecting device, and a wireless LAN system, which are capable of realizing highly reliable packet transfer.

[0005] In order to achieve the objects described above, a first embodiment of the present invention provides

a method for preventing endless transfer of a packet in a wireless LAN system, comprising the steps of:

when a packet is transferred, adding transfer history information to the received packet; when a packet is received by an interconnecting device, judging, based on transfer history information of the packet, whether or not the packet is a packet previously transferred by the interconnecting device; and transferring only a packet which is a kind of packet necessary to be transferred and which is a packet not previously transferred by the interconnecting device.

In this structure, when a previously transferred packet is received,

repeated transfer of the packet is prevented by referring to the information showing its transfer history since predetermined information showing its transfer history is added to the packet.

【0006】 A second embodiment of the present invention provides

a wireless interconnecting device which is provided in a wireless LAN system, for interconnecting a packet, the wireless interconnecting device being structured in a manner in which,

when a packet is transferred, transfer history information is added to the packet, and when a packet is received, the received packet is transferred only in a case when the packet is judged, based on transfer history information of the packet, not to be a packet previously transferred by the wireless interconnecting device and necessary to be transferred.

【0007】 A third embodiment of the present invention provides

a wireless LAN system comprising a wireless interconnecting device, in which a LAN backbone line wired with network devices is provided with wireless terminals enabled to exchange packets with wired side via the wireless interconnecting device, and in which,

the wireless interconnecting device, when transferring a packet, adds transfer history information to the packet and, when receiving a packet, transfers the received packet only in a case the packet is judged, based on transfer history information of the packet, not to be a packet previously transferred by the wireless interconnecting device and necessary to be transferred,

while, when transmitting the received packet to a terminal which is under the control of the wireless interconnecting device, the wireless interconnecting device removes the transfer history information from the packet before transmitting the packet.

BRIEF DESCRIPTION OF THE DRAWINGS

【0008】 FIG. 1 is a block diagram showing a configuration example of a wireless LAN system in an embodiment of the present invention;

FIG. 2 is a flow chart showing a procedure in the first half of a wireless VLAN packet processing in the embodiment of the present invention;

FIG. 3 is a flow chart showing a procedure starting from the step S102 in the last half of the wireless VLAN packet processing in the embodiment of the present invention;

FIG. 4 is a flow chart showing a procedure starting from the step S202 in the last half of the wireless VLAN packet processing in the embodiment of the present invention;

FIG. 5 is a flow chart showing a procedure starting from the step S302 in the last half of the wireless VLAN packet processing in the embodiment of the present invention;

FIG. 6 is a flow chart showing a procedure starting from the step S401 in the last half of the wireless VLAN packet processing in the embodiment of the present invention;

FIG. 7 (A) is an explanatory table showing an example of relationship between a MAC address and a VLAN group stored in a cable connection type wireless interconnecting device in a MAC address-based VLAN setting;

FIG. 7 (B) is an explanatory table showing an example of relationship between MAC addresses and VLAN groups stored in a first non-cable connection type wireless interconnecting device in the MAC address-based VLAN setting;

FIG. 7 (C) is an explanatory table showing an example of relationship between MAC addresses and VLAN groups stored in a second non-cable connection type wireless interconnecting device in the MAC address-based VLAN setting;

FIG. 8 is a schematic chart showing a VLAN identifier and general contents of a packet before and after the VLAN identifier;

FIG. 9 is a schematic chart showing a general format of a transferred packet;

FIG. 10 is a schematic table showing general contents of a reference table stored in a wireless interconnecting device;

FIG. 11 is a block diagram showing another configuration example of a wireless VLAN system in an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] The preferred embodiments of the present invention will now be described in detail with reference to the drawings.

Incidentally, it is to be understood that the present invention is not intended to be limited to members, dispositions, and so forth which will be described below, and various changes may be made therein without departing from the spirit of the present invention.

First, a configuration of a wireless VLAN system in an embodiment of the present invention is described with reference to FIG. 1.

The so-called hardware configuration of the wireless VLAN system of this embodiment is basically the same as that of the conventional wireless LAN system, in which a LAN backbone line 1 is provided, and various network apparatuses are connected thereto by cables. More specifically, a server 2, an administrative computer 3 and a layer 3 type wireless interconnecting device 4, and, when it is necessary, a cable connection type wireless interconnecting device 5 are connected to the LAN backbone line 1.

[0010] Further, there provided are a plurality of non-cable connection type wireless interconnecting devices connected to the layer 3 type wireless interconnecting device 4 via radio channels, and, in the configuration of this embodiment, two non-cable connection type wireless interconnecting devices, namely, the first and the second non-cable connection type wireless interconnecting devices 6A and 6B are provided.

In addition, a plurality of wireless terminals 7a to 7g are provided, which exchange packets via a radio channel with the cable connection type wireless interconnecting device 5 and the first and the second non-cable connection type wireless interconnecting devices 6A and 6B.

The server 2 is a known server which performs processing in response to requests from the terminals (clients), and the server of this embodiment may be any kind of one and does not need to be limited to a particular kind although there are various types of servers having different roles such as file servers, print servers, and so forth.

[0011] The administrative computer 3 as an administration device is a computer for administrating the entire operation of the wireless LAN system

and may serve as the above-described server 2 as well.

The layer 3 type wireless interconnecting device 4 in the embodiment according to the present invention is a conventional type wireless interconnecting device which, in other words, conforms to IEEE802.11 or IEEE802.11b and has a layer 3 switch function, and, in addition, has a so-called tagging VLAN function defined in IEEE802.1Q and further has a wireless VLAN packet processing function which will be described later.

[0012] The cable connection type wireless interconnecting device 5 in the embodiment is a wireless interconnecting device composed of a conventional type wireless interconnecting device, namely, an interconnecting device conforming to IEEE802.11 or IEEE802.11b and simply transferring packets exchanged between the wireless terminals and the wired LAN, to which added are a wireless VLAN packet processing function, which will be described later, and a MAC address-based VLAN setting function, which also will be described later. Incidentally, only one cable connection type wireless interconnecting device 5 is included in this configuration example but a configuration in which a plurality of the cable connection type wireless interconnecting devices are connected is also possible as a matter of course.

The basic configuration of the first and the second non-cable connection type wireless interconnecting devices 6A and 6B, though not conforming to IEEE802.11, are similar to that of the cable connection type wireless interconnecting device 5 described above except that the wireless interconnecting devices 6A and 6B are structured to be able to communicate with the layer 3 type wireless interconnecting device 4 via a radio channel.

[0013] The wireless terminals 7a to 7g are usually the known terminals which each are composed of a NIC (Network Interface Card) having a radio transmitting/receiving function and a computer which is represented by a mobile personal computer.

In the configuration shown in FIG. 1, the wireless terminal 7a is under the control of the cable connection type wireless interconnecting device 5, that is, the wireless terminal 7a is situated in a state where packet exchange with the cable connection type wireless interconnecting device 5 can be performed.

1054583_012202
10
5
The wireless terminals 7b to 7d are under the control of the first non-cable connection type wireless interconnecting device 6A while the wireless terminals 7e to 7g are under the control of the second non-cable connection type wireless interconnecting device 6B. Incidentally, "under the control" means that a wireless terminal is in a range where it can communicate with a wireless interconnecting device via a radio channel and is in a state where the MAC address of the wireless terminal is stored in a predetermined memory area of the wireless interconnecting device together with other information (VLAN identifiers, and so forth) as described later.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245
10250
10255
10260
10265
10270
10275
1028

predetermined memory area of each of the wireless interconnecting devices 5, 6A and 6B.

In the example described above, the relations shown in FIG. 7(A) to FIG. 7(C), for example, are stored. In the drawing, the MAC addresses are expressed in a simple form for convenience sake, wherein "xxxx1" is the MAC address of the wireless terminal 7a, "xxxx2" is the MAC address of the wireless terminal 7b, "xxxx3" is the MAC address of the wireless terminal 7c, "xxxx4" is the MAC address of the wireless terminal 7d, "xxxx5" is the MAC address of the wireless terminal 7e, "xxxx6" is the MAC address of the wireless terminal 7f, and "xxxx7" is the MAC address of the wireless terminal 7g.

[0016] As described above, the VLAN setting in the wireless interconnecting devices 5, 6A and 6B in the embodiment according to the present invention determines the VLAN groups in relation to the MAC addresses, which is a so-called MAC address-based VLAN setting.

Then, the procedure of the packet processing executed in the layer 3 type wireless interconnecting device 4, the cable connection type wireless interconnecting device 5, and the first and the second non-cable connection type wireless interconnecting devices 6A and 6B in the above described configuration is explained below referring to FIG. 2 through FIG. 10. Incidentally, in the following explanations, a general term "wireless interconnecting device" is used for the layer 3 type wireless interconnecting device 4, the cable connection type wireless interconnecting device 5, the first and the second non-cable connection type wireless interconnecting devices 6A and 6B when a common processing is executed therein while the individual names are used when a processing is executed in a particular wireless interconnecting device among the three kinds of wireless interconnecting devices described above.

[0017] When a processing starts, a wireless interconnecting device is first set in a packet receiving state in which a packet receiving is executed when a packet is inputted (see the step S010 in FIG. 2).

When a packet is received, whether the received packet is tagged or untagged is judged (see the step S012 in FIG. 2), and the processing proceeds

to the step S028 when the packet is judged to be tagged (in the case of "YES"), while the processing proceeds to a processing step S014 when the packet is judged to be untagged (in the case of "NO").

Incidentally, the tag attached to a packet is a VLAN identifier (VLAN ID) attached to a packet as shown in FIG. 8 based on the tagging VLAN function specified in IEEE802.1Q.

FIG. 8 is a schematic chart showing general contents of a packet, namely a VLAN identifier and the contents attached before and after it, in which a destination MAC address and a source (sender) MAC address are disposed in the order named from the top of the portion before the VLAN identifier, and a destination IP address is disposed after the VLAN identifier.

[0018] At the previous step S012 in FIG. 2, when the packet is judged to be tagged (in the case of "YES"), it means that the packet is a transferred packet. Then, at the step S028, a transfer AP list as transfer history information included in the received packet is obtained.

Here, to explain first, the transfer AP list, which is added to the packet when the wireless interconnecting device transfers the packet, shows transfer history of the packet. More specifically, it is inserted after the VLAN identifier explained above, for example, as shown in FIG. 9 and its contents are roughly divided from the top into a 'list length' and 'AP MAC addresses' which serve as device identifying information of devices which have transferred the packet. The 'list length' is a numerical value showing the length of the transfer AP list. Incidentally, the 'AP' mentioned here, which stands for 'Access Point', signifies a wireless interconnecting device.

The 'AP MAC addresses' are MAC addresses of wireless interconnecting devices which have transferred the packet and which are added to the packet each time the packet is transferred. In the example in FIG. 9, the AP MAC address 1 to the AP MAC address n are added, which signifies that the packet is received after being transferred by n wireless interconnecting devices. Each of the MAC addresses is added to the MAC address of a device performing an immediately preceding transfer. Specifically, in the example shown in FIG. 9, the 'AP MAC address n' is a MAC address of a wireless interconnecting device by which the last packet

transfer is performed and an 'AP MAC address (n-1)', though not shown in FIG. 9, which is disposed immediately before the 'AP MAC address n' is a MAC address of a wireless interconnecting device performing transfer of the packet immediately preceding the transfer by the wireless interconnecting device signified by the AP MAC address n.

[0019] At the step S030, the wireless interconnecting device judges whether or not its own MAC address exists in the transfer AP list previously obtained at the step S028. When its own MAC address is judged to exist in the transfer AP list (in the case of YES), which signifies that the received packet is a packet previously transferred by the wireless interconnecting device performing this processing, the series of the processing is terminated as the packet does not need to be transferred to others.

On the other hand, at the step S030, when the own MAC address is judged not to exist in the transfer AP list previously obtained at the step S028 (in the case of "NO"), which signifies that it is a packet directed to a subnet other than the VLAN group stored in the wireless interconnecting device, the destination MAC address is read out from the packet received at the previous step S010 (see the step S032 in FIG. 2).

Then, whether or not the packet previously received at the step S010 is a broadcast packet (see the step S034 in FIG. 2) is judged. Incidentally, as it is well known, whether or not a received packet is a broadcast packet is judged according to whether or not a destination MAC address included in a packet is a predetermined code.

[0020] Thereafter, the processing proceeds to the step S401 which will be described later when the received packet is judged to be a broadcast packet at the step S034 (in the case of "YES"), or to the step S302 which will be described later when the packet is judged not to be a broadcast packet (in the case of "NO") because it means that the packet is a so-called unicast. Incidentally, the processing starting from the step S302 and the processing starting from the step S401 will be described later with reference to FIG. 5 and FIG. 6 respectively.

When the received packet is judged to be untagged (in the case of "NO") at the step S012, since it means that the packet is transmitted from a

1004552.012200
20221023142007

wireless terminal belonging to the wireless interconnecting device executing the processing, a source MAC address (refer to FIG. 9) is first read out from the received packet (see the step S014 in FIG. 2). Incidentally, as cases in which a wireless interconnecting device receives a packet from a wireless terminal belonging thereto, the following cases can be thought of in the configuration shown in FIG. 1.

[0021] That is, the cases are a case in which a packet is transmitted from the wireless terminal 7b to 7g to the first or the second non-cable connection type wireless interconnecting devices 6A or 6B, and a case in which a packet is transmitted from the wireless terminal 7a to the cable connection type wireless interconnecting device 5. Incidentally, in the configuration shown in FIG. 1, packets which are exchanged between the server 2 and the layer 3 type wireless interconnecting device 4 also are untagged packets although the server 2 is not a wireless terminal under the control of the layer 3 type wireless interconnecting device 4.

Then, whether or not the source MAC address obtained at the previous step S014 exists on the reference table (refer to FIG. 10) is judged (see the step S016 in FIG. 2).

Incidentally, the reference table is a table in each of the wireless interconnecting devices 5, 6A and 6B, showing relationships of various administrative information on each of the wireless terminals 7a to 7g which are under the control of those wireless interconnecting devices. More specifically, the administrative information includes, for example, a MAC address, a VLAN identifier added to identify a VLAN group assigned on MAC address base, an IP address and a subnet mask, for each of the wireless terminals 7a to 7g. On the reference table, the administrative information is expressed in forms corresponding to the MAC addresses, for example, in the form shown in FIG. 10, and is stored in an appropriate memory area of the wireless interconnecting devices. Incidentally, the VLAN identifier may either be added automatically when a VLAN group is designated in the VLAN setting in the wireless interconnecting devices 5a, 6A and 6B as described above, or be added by a so-called manual setting.

[0022] When the source MAC address obtained at the previous step

5 S014 is judged to exist on the reference table (in the case of "YES") at the step S016, the processing proceeds to the step S024 which will be described later, while, when the source MAC address obtained at the previous step S014 is judged not to exist on the reference table (in the case of "NO"), since it means that the packet is transmitted from a wireless terminal which newly joins under the control of the wireless interconnecting device, the MAC address obtained at the step S014 is transmitted and notified to the administrative computer 3 (see the step S018 in FIG. 2). The case in which a new wireless terminal joins under the control of the wireless interconnecting device is such a case that the wireless terminal 7b is moved from under the control of the first non-cable connection type wireless interconnecting device 6A to under the control of the second non-cable connection type wireless interconnecting device 6B in the configuration shown in FIG. 1.

10
15 **[0023]** The administrative computer 3 receives the MAC address of the wireless terminal transmitted from the wireless interconnecting device by the processing at the above-described step S018 and updates a set of information for the MAC address.

20 More specifically, in the administrative computer 3, information on the MAC address, the VLAN identifier, the IP address, and the subnet of each of the wireless terminals 7a to 7g is stored in the predetermined memory area in the form of the reference table (refer to FIG. 10) explained above. Therefore, when, for example, the wireless terminal 7b moves to belong to a different wireless interconnecting device and the administrative computer 3 receives the MAC address of the wireless terminal 7b from the wireless interconnecting device to which the wireless terminal 7b newly belongs according to the processing of the step S018 previously described, the administrative computer 3 reads out the IP address and a new subnet mask of the wireless terminal 7b from the received packet as a usual course of the procedure. Then, in the administrative computer 3, the aforesaid stored data is revised, with the stored subnet mask of the wireless terminal 7b updated to the read-out new subnet mask of the wireless terminal 7b. Then, the administrative computer 3 transmits the updated contents, namely, the MAC address, the VLAN identifier, the IP address, and the subnet mask of the

wireless terminal 7b to the wireless interconnecting device to which the wireless terminal 7b newly belongs.

It is desirable that the packet exchange between the administrative computer 3 and the wireless interconnecting device is executed according to, for example, the known SNMP (Simple Network Management Protocol) in the processing at the steps S018 and S020 described above. In other words, it is appropriate to have the known SNMP manager installed in the administrative computer 3, and SNMP agent installed in the wireless interconnecting device.

[0024] Then, referring to FIG. 2 again, the information transmitted by the administrative computer 3 is received at the step S020 as described above. In other words, the VLAN identifier of the VLAN to which the wireless terminal belongs, the IP address and the subnet mask corresponding to the MAC address of the wireless terminal which becomes under the control of the new wireless interconnecting device are received.

Then, the received data is added to the reference table (refer to FIG. 10) of the wireless interconnecting device (see the step S022 in FIG. 2).

Thereafter, a destination MAC address is read out from the packet received at the previous step S010 (see the step S024 in FIG. 2).

Then, whether or not the packet received at the previous step S010 is a broadcast packet is judged (see the step 026 in FIG. 2). When the received packet is judged to be a broadcast packet (in the case of "YES"), the processing proceeds to the step S202 (refer to FIG. 4) which will be described later, while, when the received packet is judged not to be a broadcast packet (in the case of "NO"), since it means that the packet is a unicast, the processing proceeds to the step S102 (refer to FIG. 3) which will be described later.

[0025] Then, the subsequent processing will be explained below with reference to FIG. 3 for the processing starting from the step S102, to FIG. 4 for the processing starting from the step S202, to FIG. 5 for the processing starting from the step S302 and to FIG. 6 for the processing starting from the step S401 in the order named.

First, the processing starting from the step S102 is explained referring

to FIG. 3. At the step S102, since the received packet is judged to be not a broadcast packet at the previous step S026 (refer to FIG. 2), and it means that the received packet is unicast, whether or not the destination MAC address obtained at the previous step S024 (refer to FIG. 2) exists on the reference table in the wireless interconnecting device is first judged at the step S102 (refer to FIG. 3). When the destination MAC address is judged to exist on the reference table (in the case of "YES"), since it means that the packet is directed to a wireless terminal belonging to the wireless interconnecting device, the packet is transmitted with no change added, namely with no addition of a tag (VLAN identifier) by the wireless interconnecting device (see the step S108 in FIG. 3).

【0026】 When the destination MAC address obtained at the previous step S024 (refer to FIG. 2) is judged not to exist on the reference table in the wireless interconnecting device at the step S102 (in the case of "NO"), since the packet needs to be transferred, the source MAC address is first read out from the packet received at the previous step S010 (see the step S104 in FIG. 3).

Then, a VLAN identifier corresponding to the source MAC address is read out from the reference table (refer to FIG. 10) stored in the wireless interconnecting device using the source MAC address obtained at the step S104 as an index, and the VLAN identifier is then attached (see the step S106 in FIG. 3) as a tag (refer to FIG. 8) to the received packet (see the step S010 in FIG. 2). Thereafter, the own MAC address (the MAC address of the wireless interconnecting device performing this processing) is added (refer to the step S107 in FIG. 3) to the transfer AP list (refer to FIG. 9). When the own MAC address is added to the transfer AP list, the length of the transfer AP list changes due to the addition of the own MAC address, and therefore, the list length (refer to FIG. 9) is of course be revised. After that, the packet is transmitted for transferring (transfer transmission) (see the step S108 in FIG. 3), and thereby the series of the processing is terminated.

【0027】 Incidentally, the case in which a so-called tagged packet is transmitted from the wireless interconnecting device as described above includes a case where the packet is transmitted from the first or the second

non-cable connection type wireless interconnecting device 6A or 6B to the layer 3 type wireless interconnecting device 4, a case where the packet is transmitted from the cable connection type wireless interconnecting device 5 to the wired side (in other words, a case where the packet is transmitted from the cable connection type wireless interconnecting device 5 to the layer 3 type wireless interconnecting device 4) and a case where the packet is transmitted from the layer 3 type wireless interconnecting device 4 to the cable connection type wireless interconnecting device 5.

Next, the processing starting from the step S202 is explained referring to FIG. 4.

At the step S202, the destination IP address is first read out from the packet received previously at the step S010 (refer to FIG. 2) according to the judgment made at the previous step S026 (refer to FIG. 2) that the received packet is a broadcast packet.

[0028] Then, whether or not a wireless terminal belonging to the same subnetwork as the wireless terminal having the destination IP address exists on the reference table (refer to FIG. 10) is judged (see the step S204 in FIG. 4).

Incidentally, as it is generally known, the product of an IP address and a subnet mask included therein denotes a subnet (segment). Therefore, an operation is first executed based upon the above relational expression in order to find which subnetwork the destination IP address obtained at the step S202 belongs to, in other words, to find which subnet the destination IP address belongs to, and thereby a subnet is determined.

Then, whether or not a subnet to which a wireless terminal belongs is the same with the subnet to which the destination IP address obtained as described above belongs is judged one by one for the wireless terminals each having a MAC address on the reference table.

[0029] More specifically, the IP addresses are selected one by one from the reference table and a subnet is calculated by the operation described above, and whether or not the result of the calculation is the same with the subnet to which the destination IP address belongs is judged. The processing of the judgment is terminated at the point when thus calculated subnet is

judged to be the same while the same processing is executed for the next IP address on the reference table when the subnet is not the same. Thus, the processing proceeds to the step S206 when the subnet is judged to be the same (in the case of "YES") while the processing proceeds to the step S210 when it is judged for all the IP addresses on the reference table that the subnet to which the IP address belongs is not the same with the subnet to which the destination IP address belongs (in the case of "NO").

The judgment made at the step S204, that is, a wireless terminal belonging to the same subnet as the subnetwork to which the wireless terminal having the destination IP address obtained at the step S202 belongs exists on the reference table (refer to FIG. 10), means that the received packet is a directed broadcast. In other words, this case means that the received packet is a broadcast directed to a VLAN group other than the VLAN group to which the wireless terminal which transmitted the packet belongs.

[0030] Further, in this case, the packet not only needs to be transferred to another VLAN group but also needs to be transmitted to wireless terminals which are under the control of the wireless interconnecting device because the judgment "YES" made at the previous step S204 means that the wireless terminals belonging to the same subnetwork are under the control of the wireless interconnecting device.

Therefore, the VLAN identifier of the wireless terminal whose subnetwork is judged, by the processing at the previous step S204, to be the same as the subnetwork to which the wireless terminal having the destination IP address obtained at the step S202 belongs, is first obtained from the reference table (refer to FIG. 10) (see the step S206 in FIG. 4).

Then, first at the step S216, the packet is transmitted to the wireless terminal which is under the control of the wireless interconnecting device. In other words, the packet is transmitted with no VLAN identifier attached thereto in this case.

[0031] On the other hand, at the step S204, when it is judged that a wireless terminal belonging to the same subnet as the destination IP address obtained at the step S202 does not exist on the reference table (refer to FIG. 10), it means that the received packet is a limited broadcast. In other words,

1054582.01200
this case means that the packet received at the step S010 (refer to FIG. 2) is a packet transmitted from a wireless terminal belonging to the wireless interconnecting device and is directed to all other terminals in the VLAN to which the wireless terminal belongs.

5 Therefore, the received packet needs to be transmitted to wireless terminals which are under the control of the wireless interconnecting device and belong to a VLAN group to which the limited broadcast is directed, and also needs to be transferred so that it is transmitted to wireless terminals which, belonging to another wireless interconnecting device, the limited broadcast is directed to.

10 **[0032]** Then, a source MAC address is first read out from the packet received at the step S010 (see the step S210 in FIG. 4). Then, a VLAN identifier corresponding to the source MAC address, namely the VLAN identifier of the VLAN to which the wireless terminal, which transmitted the packet, belongs is obtained from the reference table (see the step S212 in FIG. 4).

15 Then, it is judged whether or not there are two or more VLAN identifiers which are the same as the VLAN identifier obtained at the above-described step S212 on the reference table, that is, whether or not there is any wireless terminal which belongs to the same VLAN group and is under the control of the wireless interconnecting device other than the wireless terminal which transmitted the packet received at the step S010 (see the step S214 in FIG. 4).

20 Thereafter, at the step S214, when it is judged that there are two or more VLAN identifiers which are the same as the VLAN identifier obtained at the step S212 on the reference table (in the case of "YES"), the processing proceeds to the step S216, so that the packet is transmitted to the wireless terminal belonging to the wireless interconnecting device.

25 **[0033]** When it is judged that there are not two or more VLAN identifiers which are the same with the VLAN identifier obtained at the step S212 on the reference table, that is, there is no wireless terminal having the same VLAN identifier other than the wireless terminal which transmits the packet received at the step S010 (in the case of "NO"), or after the processing

of the above-described step S216 is terminated, the VLAN identifier (refer to FIG. 8) obtained at the step S206 or the step S212 is first attached to the packet to be transferred to a different wireless interconnecting device (refer to FIG. 8 and the step S218 in FIG. 4). Next, the own MAC address (the MAC address of the wireless interconnecting device executing this processing) is added (refer to the step S219 in FIG. 3) to the transfer AP list (refer to FIG. 9) and the packet is transmitted for transferring by the wireless interconnecting device (see the step S220 in FIG. 4), and thereby the series of the processing is terminated. Incidentally, when the MAC address is added to the transfer AP list, the list length is revised at the same time as is previously explained (refer to the step S107 in FIG. 3).

The cases where a packet is transferred by a wireless interconnecting device includes, in the configuration shown in FIG. 1, for example, a case where the cable connection type wireless interconnecting device 5 transmits the packet to the LAN backbone line 1, a case where the first or the second non-cable connection type wireless interconnecting devices 6A or 6B transmits the packet to the layer 3 type wireless interconnecting device 4, a case where the layer 3 type wireless interconnecting device 4 transmits the packet to the LAN backbone line 1 and a case where the layer 3 type wireless interconnecting device 4 radio-transmits to the first and the second non-cable connection type wireless interconnecting devices 6A and 6B.

【0034】 Next, the processing starting from the step S302 is explained referring to FIG. 5.

At the step S302, whether or not the destination MAC address obtained by the processing at the previous step S032 (refer to FIG. 2) exists on the reference table (refer to FIG. 10) is judged. At the step S302, when it is judged that the destination MAC address obtained by the processing at the step S032 does not exist on the reference table (in the case of "NO"), since it means that no wireless terminal to which the received packet needs to be transmitted, exists under the control of the wireless interconnecting device, the packet received at the step S010 (refer to FIG. 2) is transmitted for transferring (transmission for transferring) with no change added (see the step S306 in FIG. 5).

When it is judged at the step S302 that the destination MAC address obtained by the processing at the step S032 (refer to FIG. 2) exists on the reference table (in the case of "YES"), since it means that the packet received at the step S010 (refer to FIG. 2) needs to be transmitted to a wireless terminal
5 belonging to the wireless interconnecting device, the tag (VLAN identifier) attached to the received packet is removed (refer to the step S304 in FIG. 5). Then, the transfer AP list (refer to FIG. 9) is removed from the packet (refer to the step S305 in FIG. 5) and the packet is transmitted to the wireless terminal (refer to the step S306 in FIG. 5), and thereby the series of the processing is
10 terminated.

[0035] Next, the processing starting from the step S401 is explained referring to FIG. 6.

At the step S401, the own MAC address (the MAC address of the wireless interconnecting device executing this processing) is first added to the transfer AP list before the packet is transferred. When the MAC address is
15 added to the transfer AP list, the list length is revised at the same time as previously explained (refer to the step S107 in FIG. 3).

Next, at the step S402, the received packet is transmitted for transferring to other wireless interconnecting devices corresponding to the
20 judgment that the received packet is a broadcast packet (see the step S034 in FIG. 2)

Then, a destination IP address is read out from the received packet (see the step S404 in FIG. 6) and judgment is made whether or not a wireless terminal belonging to the same subnetwork as the wireless terminal having
25 the destination IP address exists on the reference table (refer to FIG. 10) (see the step S406 in FIG. 6). Incidentally, since the specified procedure of the judgment whether or not a wireless terminal belonging to the same subnetwork exists on the reference table is the same as the one described previously at the step S204 (refer to FIG. 4), it is not described here again.

[0036] Then, at the step S406, when it is judged that a wireless
30 terminal belonging to the same subnet as the wireless terminal having the destination IP address obtained from the received packet exists on the reference table (in the case of "YES"), since it means that the wireless

terminal to which the received packet is to be transmitted is under the control of the wireless interconnecting device, the tag (VLAN identifier) which is attached to the received packet is removed and the transfer AP list(refer to FIG. 9) is also removed (refer to the steps S412 and S413 in FIG. 6).
5 Thereafter, the packet is transmitted to the wireless terminal (see the step S414 in FIG. 6). Thereby, the series of the processing is finished.

When it is judged at the step S406 that a wireless terminal belonging to the same subnetwork as the wireless terminal having the destination IP address obtained from the received packet does not exist on the reference
10 table (in the case of "NO"), it means that the packet is a limited broadcast as previously described at the step 204.

Therefore, a VLAN identifier is first read out (see the step S408 in FIG. 6) from the received packet, and then whether or not the VLAN identifier exists on the reference table is judged (see the step S410 in FIG. 6).

15 **【0037】** When the VLAN identifier is judged to exist on the reference table (in the case of "YES") at the step S410, since it means that a wireless terminal to which the received packet is to be transmitted exists under the control of the wireless interconnecting device, the aforesaid steps S412 and S413 are executed and then the packet is transmitted to the wireless terminal.
20 Thereby, the series of the processing is terminated (see the step S414 in FIG. 6).

When the VLAN identifier is judged not to exist on the reference table (in the case of "NO") at the step S410, since it is not necessary to transmit the packet to a wireless terminal which is under the control of the wireless
25 interconnecting device, the series of the processing is terminated.

30 **【0038】** Thus, the wireless VLAN packet processing described above is executed in the layer 3 type wireless interconnecting device 4, the cable connection type wireless interconnecting device 5, the first and the second non-cable connection type wireless interconnecting devices 6A and 6B, so that the wireless terminals 7a to 7g can be moved freely for operation among the cable connection type wireless interconnecting device 5, the first and the second non-cable connection type wireless interconnecting devices 6A and 6B. To be more specific, for example, it is assumed that the wireless terminal 7b is

moved from a state where it is under the control of the first non-cable connection type wireless interconnecting device 6A, namely, a state where it is in the communication range of the first non-cable connection type wireless interconnecting device 6A, to the communication range of the second non-cable connection type wireless interconnecting device 6B, and transmits a packet. It is further assumed that the first and the second non-cable connection type wireless interconnecting devices 6A and 6B are conventional type of wireless interconnecting devices, namely, wireless interconnecting devices which only have the function of simply transferring packets within a subnet, not having the wireless VLAN packet processing function which is described above referring to FIG. 2 to FIG. 6. In this case, if the wireless terminal 7b is moved to the communication range of the second non-cable connection type wireless interconnecting device 6B and transmits packets, the communication between the second non-cable connection type wireless interconnecting device 6B and the wireless terminal 7b is conventionally impossible with no function added because the first non-cable connection type wireless interconnecting device 6A and the second non-cable connection type wireless interconnecting device 6B belong to different subnets. It has been made possible for the wireless terminal 7b to communicate with the second non-cable connection type wireless interconnecting device 6B only by resetting the IP address of the wireless terminal 7b.

[0039] On the other hand, in the embodiment of the present invention, the step S014 and subsequent processing (refer to FIG. 2) are executed when the wireless terminal 7b is moved as described above, so that the wireless terminal 7b can communicate with the second non-cable connection type wireless interconnecting device 6B without setting a new IP address unlike the conventional system. In addition, the move of the wireless terminal 7b is notified to the administrative computer 3 (see the step S018 in FIG. 2), so that the administrative computer 3 can track the location of the wireless terminal 7b.

In other words, in the conventional system, wireless terminals which are under the control of the same wireless interconnecting device usually have to belong to only one subnet. That is, wireless terminals which belong to

different subnets are not allowed to exist under one wireless interconnecting device. On the other hand, in the embodiment of the present invention, it becomes possible that wireless terminals belonging to different subnets exist under the control of one wireless interconnecting device.

Furthermore, in the embodiment of the present invention, when a packet is transferred, the MAC address of a device transferring the packet is added to the transfer AP list which is included in the packet so that the transfer history of the received packet can be confirmed, and thereby, it can be prevented that the same wireless interconnecting device repeatedly transfers the same packet.

[0040] Incidentally, the packet types exchanged in the above-described configuration are as follows: untagged packets are exchanged between the layer 3 type wireless interconnecting device 4 and the server 2 while tagged packets are exchanged between the layer 3 type wireless interconnecting device 4 and the administrative computer 3, and between the layer 3 type wireless interconnecting device 4 and the cable connection type wireless interconnecting device 5.

Tagged packets are exchanged between the layer 3 type wireless interconnecting device 4 and the first and the second non-cable connection type wireless interconnecting devices 6A and 6B, and untagged packets are exchanged between the first and the second wireless interconnecting devices 6A and 6B and the wireless terminals 7b to 7g.

Between the cable connection type wireless interconnecting device 5 and the wireless terminal 7a, untagged packets are exchanged.

[0041] Next, another configuration example of the wireless LAN system is explained referring to FIG. 11. Incidentally, the same reference numerals and signs will be used to designate the same or similar components as those shown in FIG. 1, so that the detailed description will be omitted, and differences are mainly described below.

In the configuration shown in FIG. 1, the layer 3 type wireless interconnecting device 4 is used. However, the layer 3 type wireless interconnecting device 4 is not always necessary and a configuration in which only the cable connection type wireless interconnecting devices 5a and 5b as

wireless interconnecting devices are connected to the LAN backbone line 1 (refer to FIG. 13) is also possible. That is, the cable connection type wireless interconnecting devices 5a and 5b have the same function as the cable connection type wireless interconnecting device 5 in the configuration example shown in FIG. 1.

【0042】 Incidentally, since the packet processing executed by the cable connection type wireless interconnecting devices 5a and 5b in the configuration is basically the same with the processing described above with reference to FIG. 2 to FIG. 10, it will not be described in detail here again.

As described above, according to the present invention, the predetermined information showing the transfer history is added to a packet when the packet is transferred, so that a packet is surely prevented from being repeatedly transferred by referring to the information showing its transfer history when a packet previously transferred by the same wireless interconnecting device is received. This makes it possible to reduce unnecessary traffic and thereby, the effect that a highly reliable wireless LAN system can be provided is brought about.